

**BORING MACHINES**  
**WOTAN RAPID 3 - DIAM. 160**



**BORING MACHINES**  
**WOTAN RAPID 3 - DIAM. 160**



**BORING MACHINES**

**WOTAN RAPID 3 - DIAM. 160**



- SPINDLE BORE DIAMETER: 160 mm**
- Y AXIS TRAVEL (VERTICAL): 3000 mm**
- X AXIS TRAVEL (LONGITUDINAL): 6000 mm**
- Z AXIS TRAVEL (QUILL): 1000 mm**
- CNC ROTOTRASLATION TABLE DIMENSION: 2000 x 2500 mm**
- B AXIS: 360.000 positions**
- W AXIS: 2500 mm**
- MAX LOAD CAPACITY: 20 ton**
- SPINDLE NOSE TAPER: ISO 50**
- SPINDLE MOTOR POWER: 63/28 kw**
- SPINDLE SPEED ROTATION: 2,5 - 1000 rpm**
- SPINDLE MILL DIAMETER: 280 mm**
- FEEDS: 1 - 2000 mm/min**
- RAPID FEEDS: 10 mt/min**
- ACCESSORIES: spindle extension, vertical head**
- CNC: machine to retrofit**

**THE DATA ARE NOT TO UNDERSTAND ENGAGED**