BORING MACHINES - T TYPE BORER - PEGARD

PEGARD PRECIVIT 2 pallet - 6 axis - U axis integrated



Condition:
SPINDLE DIAM: **110 mm**
X AXIS TRAVEL: **1600 mm**
Z AXIS TRAVEL: **650 mm (spindle)**
Y AXIS TRAVEL: **1200 mm**
W AXIS TRAVEL: **1600 mm**
U AXIS (faceplate) : **200 mm**
TABLE DIMENSIONS: **1100 x 1200 mm**
MAX LOAD CAPACITY: **5 ton**
TABLE DIVISION: **360.000 pos**
SPINDLE NOSE TAPER: **ISO 50**
SPINDLE MOTOR POWER: **26 kw**
SPINDLE SPEED: **40 -2000 rpm**
ATC: **84 pos**
FACEPLATE DIAM: **600 mm**
FACEPLATE POSITIONS NR : **1**
FACE PLATE SPEED: **4 - 355 rpm**
FACE PLATE BORE: **30-600 mm**
CNC: **ECS 2700 D**
U AXIS RAPID FEEDS: **2 m/min**

Non-binding data

S.S. per Voghera, Loc. Capitania 97/C/2, 15057 - Tortona (AL) – T +39 0131 814498 - Fax – Vat Id IT01105170060 – info@selemarc.com - www.selemarc.com