

PEGARD PRECIVIT 2 PTX - 6 axis - U axis integrated



Condition:

SPINDLE DIAM: 130

X AXIS TRAVEL: 2250 mm

Z AXIS TRAVEL: 950 mm

Y AXIS TRAVEL: 1800 mm

W AXIS TRAVEL: 1800 mm

U AXIS TRAVEL (faceplate): 200 mm

TABLE DIMENSIONS: 1420 X 2000 MM

MAX LOAD CAPACITY: 12 ton

TABLE DIVISION: 360.000 pos

SPINDLE NOSE TAPER: ISO 50

SPINDLE MOTOR POWER: 33 kw

SPINDLE SPEED: 16 - 1250 rpm

ATC: 36 positions

X AXIS RAPID FEEDS: 10 m/min

Y AXIS RAPID FEEDS: 10 m/min

W AXIS RAPID FEEDS: 10 m/min

FACEPLATE DIAM: 700 mm

FACEPLATE POSITIONS NR : 2

FACEPLATE BORING: 30 - 1100 mm

FACE PLATE SPEED: 4 - 315 rpm

SECONDARY RAM WITH VERTICAL HEAD: 250 x 250 mm

SECONDARY RAM TRAVEL: 1400 mm

SECONDARY RAM SPINDLE NOSE: ISO 40

CNC: ECS 2101

Non-binding data