BORING MACHINES - TABLE TYPE BORER - PEGARD

PEGARD PRECIVIT 2 PTX - 6 axis - U axis integrated



Condition:
SPINDLE DIAM: **130**
X AXIS TRAVEL: **2250 mm**
Z AXIS TRAVEL: **950 mm**
Y AXIS TRAVEL: **1800 mm**
W AXIS TRAVEL: **1800 mm**
U AXIS TRAVEL (faceplate): **200 mm**
TABLE DIMENSIONS: **1420 X 2000 MM**
MAX LOAD CAPACITY: **12 ton**
TABLE DIVISION: **360.000 pos**
SPINDLE NOSE TAPER: **ISO 50**
SPINDLE MOTOR POWER: **33 kw**
SPINDLE SPEED: **16 - 1250 rpm**
ATC: **36 positions**
X AXIS RAPID FEEDS: **10 m/min**
Y AXIS RAPID FEEDS: **10 m/min**
W AXIS RAPID FEEDS: **10 m/min**
FACEPLATE DIAM: **700 mm**
FACEPLATE POSITIONS NR : **2**
FACEPLATE BORING: **30 - 1100 mm**
FACE PLATE SPEED: **4 - 315 rpm**
SECONDARY RAM WITH VERTICAL HEAD: **250 x 250 mm**

S.S. per Voghera, Loc. Capitania 97/C/2, 15057 - Tortona (AL) – T +39 0131 814498 - Fax – Vat Id IT01105170060 – info@selemarc.com - www.selemarc.com

SECONDARY RAM TRAVEL: **1400 mm**
SECONDARY RAM SPINDLE NOSE: **ISO 40**
CNC: **ECS 2101**

Non-binding data

S.S. per Voghera, Loc. Capitania 97/C/2, 15057 - Tortona (AL) – T +39 0131 814498 - Fax – Vat Id IT01105170060 – info@selemarc.com - www.selemarc.com