

KOLB HTB 3



Condition:

MAX DRILL DIAM : 65 mm

MAX DRILL DIAM WITH PRE-DRILL: 80 mm

MAX DRILL DIAM WITH 3 SPINDLES: 32 mm

X TRAVEL: 5000 mm

Y TRAVEL: 3000 mm

Z TRAVEL: 1100 MM (+ 500 MM)

DISTANCE OF THE 3 SPINDLES ONE FROM THE OTHER: MIN 250 MM / MAX 400 MM

MAIN SPINDLE WORKING AREA: 5000 X 3000 MM

WORKING AREA WITH 3 SPINDLES MINIMUM DISTANCE: 5000 X 3500 MM

WORKING AREA WITH 3 SPINDLES MAX DISTANCE: 5000 X 3800 MM

SPINDLE NOSE TAPER: ISO 50

SPINDLE MOTOR POWER: 40 KW

SPINDLE SPEED: 36-900 RPM / 112-2800 RPM

N.3 SPINDLE SPEED: 45-1120 RPM / 112-2800 RPM

RAPID FEEDS: 5000 MM/MIN

CNC: SIEMENS 550 C

OTHER DETAILS: BTA and GUN DRILL

ACCESSORIES:

2 ANGLE PLATES 1800 x 1900 x h 4000, weight 14.500 kg each one - 2 FLOOR PLATES 6000 x 1500 x h 390 each one

Non-binding data